



**MODEL CODE SELECTOR - FIELD^{IT}
ACTUATORS & POSITIONERS
INTELLIGENT POSITIONERS
TYPE TZID, TZID Ex, TZID SS**

Model Code	TZID	01 - 04	05	06	07	08	09	10	11	
TZID Intelligent Positioner		TZID								
Housing										
Aluminum with epoxy coating: NEMA 4X, IP 65		A								
Stainless Steel (315, 1.4581): NEMA 4X, IP 65		S								
Actuator Type										
Linear, 0.4" to 3.3" (10 to 85 mm) stroke (Aluminum Housing)		5								
Linear, 0.4" to 3.3" (10 to 85 mm) stroke (SS Housing)		5								
Linear, 0.4"-3.3"stroke (Aluminum Housing) Remote Mounted Electronics		Y								
Rotary, 90° rotation, NAMUR-VDI/VDE 3845 (Alum. Housing)		6								
Rotary, 90° rotation, NAMUR-VDI/VDE 3845 (SS Housing)		7								
Rotary, 90° rotation, NAMUR-VDI/VDE 3845 (Aluminum Housing) Remote mounted electronics		Z								
Agency Certification										
General Purpose		0								
ATEX I.S. Eex ia IIC		1								
ATEX I.S. Eex ia IIC with flammable gas air supply (Alum. Housing)		2								
FM Intrinsically Safe/Non-Incendive CL I, II, III; Div 1,2 Gr A-G		3								
British Standards Non-Incendive EX N IIC		4								
ATEX I.S. Eex ia IIC with flammable gas air supply (SS Housing)		5								
Control Action/Failure Mode on Loss of 4-20 mA Input										
Single Acting/Fail Open/Close		1								
Single Acting/Fail-in-Place		2								
Double Acting/Fail Open/Close		4								
Double Acting/Fail-in-Place		5								
Connections										
Electrical: 1/2-14 NPT Pneumatic: 1/4-18 NPT (Required for FM units)		2								
Electrical: Pg. 13.5 Pneumatic: 1/4-18 NPT		3								
Electrical: M20 x 1.5 Pneumatic: M12x1		4								
Electrical: M20 x 1.5 Pneumatic: 1/4-18 NPT		5								
Position Feedback Module¹										
Analog 4-20 mA FM/CSA approved, I.S., Non-incendive CI I, II, III; Div. 1, 2; Gr A-G		2								
Digital output (3) for min/max and general alarm FM/CSA approved		6								
None (but with Proximity Limit Switches) Select from 2 or 4 below		8								
None		9								
Mechanical Limit Switches²										
None		0								
Two P&F slot-type proximity switches (Normally Closed)		2								
Two P&F slot-type proximity switches (Normally Open)		4								

1. Note that Option Code 1 in this field is for a standard purpose 4-20mA feedback module. Option 2 is offered in place of the general purpose.

2. TZID with mechanical limit switches is only ATEX approved.

Standard Product =



**MODEL CODE SELECTOR - FIELD^{IT}
ACTUATORS & POSITIONERS
INTELLIGENT POSITIONERS
TYPE TZID, TZID Ex, TZID SS**

Accessories

Mounting Hardware

Mounting Kit for linear actuators, stroke 0.4 to 3.3" (designed to IEC534-1 or NAMUR)	0319601
Optional Feedback arm for linear strokes greater than 3.3" (strokes 0.4" to 5.9")	0319602
Mounting Bracket for rotary actuators, 90°, (designed to VDI-VDE 3845)	
80/20 mm	0319603
80/30 mm	0319604
130/30 mm	0319605
130/50 mm	0319606
Mounting Kit for Neles BC/BJ	7959096
Mounting Kit for Neles BC/U & BJ/U	7959097
Mounting Kit for Foxboro V724/V726/V713	0319601
Mounting Kit for Fisher 657A/667	7959155
Mounting Kit for Fisher 1051/30 & 1052/30	7959135
Mounting Kit for Fisher 1051/60 & 1052/60	7959169
Mounting Kit for Bettis RPC/CBA/G Series	0319603
Mounting Kit for Masoneilan Rotopact 400-90	7958312
Mounting Kit for Masoneilan Varipak 28000	7959164
Mounting Kit for Masoneilan Camflex II & Varimax 30000	0319641

Pressure Gauge Block

For single-acting output (with 1 pressure gauge for air supply and 1 pressure gauge for output pressure) Connections 1/4-18 NPT, supply air pressure range 0-10 bar / 0-140 psi	
Output pressure range 0-4 bar / 0-60 psi aluminum version ²	18391 - 7959064
Output pressure range 0-4 bar / 0-60 psi stainless steel version ³	18391 - 7959067
Output pressure range 0-10 bar / 0-140 psi aluminum version ²	7959030
Output pressure range 0-10 bar / 0-140 psi stainless steel version ³	7959045
For double-acting output (with pressure gauge for air supply and 2 pressure gauges for output pressure) Connections 1/4-18 NPT, supply air pressure range 0-10 bar / 0-140 psi	
Output pressure range 0-4 bar / 0-60 psi aluminum version ²	18391 - 7959065
Output pressure range 0-4 bar / 0-60 psi stainless steel version ³	18391 - 7959069
Output pressure range 0-10 bar / 0-140 psi aluminum version ²	7959031
Output pressure range 0-10 bar / 0-140 psi stainless steel version ³	7959046

Regulator (1/4 - 18 NPT connections)

Parker No. 05R118AD	1951029_5
---------------------	-----------

Filter (1/4 - 18 NPT connections)

Parker No. 15F14HA	5328563_2
--------------------	-----------

Notes:

1. The pressure gauge blocks are delivered as separate units for self-assembly.
2. Aluminum version: Aluminum pressure gauge block, painted black (like case) pressure gauges with black plastic case.
3. Stainless Steel Version: Pressure gauge block made of stainless steel 1.4571 pressure gauges with stainless steel case.
4. Stainless steel filter regulator not available.

Standard Product =



**MODEL CODE SELECTOR - FIELD^{IT}
ACTUATORS & POSITIONERS
INTELLIGENT POSITIONERS
TYPE TZID, TZID Ex, TZID SS**

Accessories - (continued)

Communication Devices	
Local Communication adapter for RS 232 connection (LCI)	18389 - 0319621
HART® Communication modem for USB Connection	010031F
HART® Communication modem	010001F
SmartVision 4 CD-ROM	SM401-1
Spare Parts Modules	
I/P Module, Single Acting Fail Open/Close	18381-0-0010000
I/P Module, Single Acting Fail In Place	18381-0-0020000
I/P Module, Double Acting, Fail Open/Close	18381-0-0040000
I/P Module, Double Acting, Fail In Place	18381-0-0050000
4-20 mA Position Feedback Module	18381-0-0000400
4-20 mA Position TX with for 48V supply	18391-7959193
Digital Position Feedback Module no IS protection	18381-0-0000600
Instruction Bulletin	
(One copy supplied with order at no charge)	42/18-54.1 EN

CF = Consult Factory

Standard Product =